

**AMENDMENTS TO THE CLAIMS**

**This listing of claims will replace all prior versions and listings of claims in the application:**

**LISTING OF CLAIMS:**

1. (Currently amended): A program guide displaying apparatus comprising:

a program information obtaining device for obtaining program information including information indicative of a program name, a genre name, a start time, a length of a program or an end time, a broadcasting channel and a broadcasting date of a respective one of a plurality of programs;

a program information displaying device for displaying the program information as-for the programs on a first program table in a first display mode or on a second program table in a second display mode which are exchangeable ~~to~~ with each other,

wherein said program information displaying device displays the program information in such a manner that in the first display mode the programs are distinguishable from each other by colors set for respective genres of the programs for a first time range on a time axis and a first channel range on a channel axis ~~in the first display mode~~, and ~~that~~ in the second display mode the programs are distinguishable from each other by at least program names ~~of the programs~~ for a second time range, which is narrower than the first time range, on the time axis, and a second channel range, which is narrower than the first channel range, on the channel axis ~~in the second display mode~~;

a table range displaying device for displaying on the second program table in the second display mode ~~a second program table~~ a program range surrounding a plurality of program cells which were displayed on [[a]] the first program table ~~displayed in the first display mode;~~

a movement specifying device for receiving an instruction to move the program table program range; and

a moving device for moving the second program table program range ~~on~~ to the first program table in response to the instruction received by said movement specifying device,

wherein said moving device moves the second program table program range for a distance equivalent to a ~~predetermined~~ specified number of unit-time-periods in a time axis direction and a ~~predetermined~~ specified number of channels in a channel axis direction,

wherein the program guide displaying apparatus further comprises a mode specifying device for receiving an instruction to change between the first display mode and ~~into~~ the second display mode,

wherein the table displaying device changes between the first display mode and the second display mode in response to the instruction received by the mode specifying device, ~~and~~

wherein the program names within the second program table are displayed in the second display mode, and

wherein the program information displaying device displays the program information, which is specified by the program range, on the second program table in the second display mode in response to the instruction received by the mode specifying device.

2. (Currently amended): A program guide displaying apparatus according to claim 1, wherein the program information displaying device further displays the program information in a third display mode in such a manner that the program information is indicated as a popup display, which is displayed at a vicinity of a program cell which is currently selected on the first program table in the first display mode and indicates information related to the program corresponding to the selected program cell,

wherein the popup display is displayed at a position determined in correspondence with a position of the selected program cell in the first program table,

wherein the mode specifying device further receives an instruction to change between the first display mode and ~~into~~ the third display mode, and

wherein the table displaying device changes between the first display mode and the third display mode in response to the instruction by received by the mode specifying device, and

wherein the program information displaying device displays the program information in the second display mode in response to the instruction received by the mode specifying device.

3. (Currently amended): A program guide displaying method comprising:

a program information obtaining process of obtaining program information including information indicative of a program name, a genre name, a start time, a length of a program or an end time, a broadcasting channel and a broadcasting date of a respective one of a plurality of programs;

a program information displaying process of displaying the program information ~~as for~~ the programs on a first program table in a first display mode or on a second program table in a second display mode which are exchangeable ~~to~~ with each other,

wherein said program information displaying process displays the program information in such a manner that in the first display mode the programs are distinguishable from each other by colors set for respective genres of the programs for a first time range on a time axis and a first channel range on a channel axis ~~in the first display mode~~, and that in the second display mode the programs are distinguishable from each other by at least program names ~~of the programs for~~ a second time range, which is narrower than the first time range, on the time axis and a second channel range, which is narrower than the first channel range, on the channel axis ~~in the second display mode~~;

a table range displaying process of displaying on the second program table in the second display mode ~~a second program table~~ a program range surrounding a plurality of program cells which were displayed on ~~[[a]] the first program table displayed in the first display mode~~;

a movement specifying process of receiving an instruction to move the program table program range; and

a moving process of moving the second program table program range ~~on to~~ the first program table in response to the instruction received by said movement specifying process,

wherein said moving process moves the second program table program range for a distance equivalent to a specified ~~predetermined~~ number of unit-time-periods in a time axis direction and a specified ~~predetermined~~ number of channels in a channel axis direction,

wherein the program guide displaying method further comprises a mode specifying process of receiving an instruction to change between the first display mode and ~~into~~ the second display mode,

wherein the table displaying process changes between the first display mode and the second display mode in response to the instruction by received by the mode specifying process, and

wherein the program names within the program table are displayed in the second display mode, and

wherein the program information displaying process displays the program information, which is specified by the program range, on the second program table in the second display mode in response to the instruction received by the mode specifying process.

4. (Currently amended): A program guide displaying method according to claim 3, wherein the program information displaying process further displays the program information in a third display mode in such a manner that the program information is indicated as a popup display; which is displayed at a vicinity of a program cell which is currently selected on the program table in the first display mode and indicates information related to the program corresponding to the selected program cell,

wherein the popup display is displayed at a position determined in correspondence with a position of the selected program cell in the program table,

the mode specifying process further receives an instruction to change between the first display mode and ~~into~~ the third display mode, and

the table displaying process changes between the first display mode and the third display mode in response to the instruction by received by the mode specifying process, and  
wherein the program information displaying process displays the program information in the second display mode in response to the instruction received by the mode specifying process.

5. (Previously presented): The apparatus of claim 1, wherein the first program table displayed on the first display mode comprises the first time range and the first channel range and the second program table displayed on the second display mode comprises the second time range and the second channel range, and

wherein the second program table displayed on the second display mode corresponds to a subset of the first program table displayed on the first display mode.

6. (Previously presented): The method of claim 3, wherein the first program table displayed on the first display mode comprises the first time range and the first channel range and the second program table displayed on the second display mode comprises the second time range and the second channel range, and

wherein the first program table displayed on the second display mode corresponds to a subset of the second program table displayed on the first display mode.